

DIY SPRAYSTONE

**ELECTRIC SPRAYGUN
MODEL: PLD3151S**

HERE ARE THE EASY STEPS FOR APPLICATION OF THE PRODUCT. READ CAREFULLY BEFORE USING.

- 1- Clean the surface to be painted completely of any imperfections and/or dirt and repair the damaged surface if necessary before starting.
- 2- Using the electric sprayer be sure to set the 1.5mm nozzle to apply a primer for interior or exterior (inquire advice from a retailer on the primer to be used depending on the surface to be painted); a single coat will be required at this step. Allow the primer to dry thoroughly before applying paint. The drying time may vary depending on the moisture content of each room/surface. Make sure that the primer bonds firmly to the surface/coating for optimal results.
- 3- If the primer does not adhere firmly to the surface even after leaving it to dry thoroughly, Leadvision will not guarantee the results.

WARNING: SOME SURFACES MAY BE INCOMPATIBLE (FOR REASONS BEYOND OUR KNOWLEDGE).

- 4- Thoroughly clean the sprayer with water between each application for an optimal result (refer to the user manual). As all products DIY SprayStone are water-based, cleaning will be easy.
- 5- Before applying the product, you must gently mix with a ladle (do not use an electric stirrer) to avoid damaging the paint particles. You must mix until you obtain a thick and smooth liquid.

- 6- Important: Before you start filling your electric sprayer, you must change the 1.5mm nozzle for the 3.5mm nozzle and 3.5mm spray tip that is in the accessory bag.
- 7- Before starting your project, make sure that the container of your sprayer is filled with paint. Then, plug the power cord of the sprayer into the wall outlet, making sure that there is no risk of injury.
- 8- For interior application, we suggest 2 coats and 3 coats for exterior application (may vary depending on the location or surface to be painted).
- 9- The first layer will be applied in 2 steps. First, you must put the nozzle of the electric sprayer in a horizontal position (see image in ref.1). Paint the complete surface in a 1. horizontal motion (from left to right). Step two, you must put the nozzle of the electric sprayer in a 2. vertical position (see image in ref.1). Paint the same surface but in a vertical movement (from top to bottom). You do not have to wait for a complete drying between these two steps. Important: always keep a minimum distance of 12" and a maximum distance of 18" between the electric sprayer and the surface to be painted. The application should not be done too quickly. For spaces that require more precision, place the nozzle of the electric sprayer in a 3. diagonal position (see image in ref.1)

- 10- The first coat has just been applied. You can take advantage of this drying time (the time may vary according to location) to clean the electric sprayer (refer to the maintenance guide for cleaning). The color of the painted surface will change as the product dries until the desired result is achieved.
- 11- For the second coat, once your surface is dry, repeat the same procedure from step 9 to from step 10.
- 12- If a third coat is required inside (depending on the place of application) or mandatory outside, repeat step 9 and step 10.
- 13- For maximum protection (water, dirt, additional UV protection, etc.) you must apply the DIY SprayStone sealer coating.
- 14- For application of a sealer, a single coat will be required by following the same procedure as in steps 9-10.
- 15- For the full warranty or any questions regarding products, please refer to our website www.leadvisioninternational.com

REF. 1

